

## EFFICIENT 13 SEER HEAT PUMP ENVIRONMENTALLY SOUND R-410A REFRIGERANT

1½ THRU 5 TONS SPLIT SYSTEM

208 / 230 Volt, 1-phase, 60 Hz

### REFRIGERATION CIRCUIT

- Copeland Scroll® compressors on all models
- Suction line accumulator factory installed
- Bi-flow filter-drier included for field installation
- Integrated solid state control with Time-Temperature Defrost
- High and low pressure switches
- Copper tube / aluminum fin coil

### PERFORMANCE

- Two-speed fan motors factory wired on all models
- Compressor Sound Jacket standard

### EASY TO INSTALL AND SERVICE

- Comfort Alert™ Diagnostics device on all models
- Easy access service valves on all models
- Innovative control box design
- External high and low refrigerant service ports
- Fan motor in-line disconnect plug
- Only two screws to access control panel
- Factory charged with R-410A refrigerant

### BUILT TO LAST

- High gloss, baked-on powder coat finish over galvanized steel
- Post-painted (black) coil fins
- Coated, weather-resistant cabinet screws
- Coated inlet grille with 3/8" (10mm) spacing for extra protection (hail guard)
- Corner posts for extra strength and style

### WARRANTY\*

- 1 year No Hassle Replacement™ limited warranty
- 5 year compressor limited warranty
- 5 year parts limited warranty (including compressor and coil)
- With timely registration, an additional 5 year parts limited warranty (including compressor and coil)

\* For owner occupied, residential applications only. See warranty certificate for complete details and restrictions, including warranty coverage for other applications



Use of the AHRI Certified TM Mark indicates a manufacturer's participation in the program. For verification of certification for individual products, go to [www.ahridirectory.org](http://www.ahridirectory.org).

### UNIT PERFORMANCE DATA

Model Number	Size (tons)	Nominal Btu/hr	Min. Circuit Ampacity	Max. Fuse or Breaker	Operating Dimensions height x width x depth in. (mm)	Ship / Operating Weight lbs. (kg)	Notes
C4H318GKD	1-1/2	18,000	11.9	20	28-9/16 x 31-3/16 x 31-3/16 (726 x 793 x 793)	202 / 167 (92 / 76)	
C4H324GKD	2	24,000	16.7	25	28-9/16 x 31-3/16 x 31-3/16 (726 x 793 x 793)	203 / 167 (92 / 76)	
C4H330GKE	2-1/2	30,000	21.1	30	28-9/16 x 31-3/16 x 31-3/16 (726 x 793 x 793)	180 / 146 (82 / 66)	
C4H336GKE	3	36,000	22.0	35	32 x 31-3/16 x 31-3/16 (813 x 793 x 793)	178 / 152 (81 / 69)	
C4H342GKE	3-1/2	42,000	25.7	40	28-9/16 x 31-3/16 x 31-3/16 (726 x 793 x 793)	229 / 193 (104 / 88)	
C4H348GKE	4	48,000	28.7	50	35-3/8 x 31-3/16 x 31-3/16 (899 x 793 x 793)	251 / 216 (113 / 98)	
C4H360GKD	5	60,000	34.1	50	29-7/8 x 35 x 35 (760 x 889 x 889)	293 / 252 (133 / 114)	